



NUC-CMO

4G/LTE Multiband & MIMO Puck Antenna

Features

- Low Profile Puck Antenna
- 2 x 4G/LTE Multiband elements
- Permanent Mount
- Fully Waterproof when mounted

Specifications

	Element 1	Element 2
Frequency range	690-800/ 800-960 / 1710-2170 / 2500-2700 MHz	690-800/ 800-960 / 1710-2170 / 2500-2700 MHz
Peak Gain	1 / 2.5 / 3.8 / 5 dBi	1 / 2.5 / 3.7 / 5 dBi
VSWR	<3.0:1	<2.5:1
Polarisation	Linear	Linear
Power rating	10 W	10W
Impedance	50 Ohms	50 Ohms
Dimensions	102 x 33.5mm (dxh)	

Ordering Options

NUC-CMO-1M	CMO antenna with 2 x 1M RG174 and SMA-Male
NUC-CMO-2M	CMO antenna with 2 x 2M RG174 and SMA-Male
NUC-CMO-3M	CMO antenna with 2 x 3M RG174 and SMA-Male

Specifications subject to change without notice.

Nucleus Networks Limited
Horizon
Honey Lane
Hurley SL6 6RJ

Tel: +44 (0)20 8819 8550
Fax: +44 (0) 845 868 3625
Email: shop@nucleusnetworks.co.uk
Web: www.nucleusnetworks.co.uk